



QUADRALUMEN
LED by life


Product TDS

Model No.: QL7001RG

Description: QL LED Bulb

Trademark: Aurus™

Product Dimensions



Product Image



System Wattage (Watts)	Input Voltage (AC)	Power Factor (PF)	THD	Driver Surge Protection	CCT Available	Diameter (MM)	Height (MM)
3w	90-300	0.50	-	2.5Kv	3000k 6500k	44	80
5w		> 0.90	<15%			54	101
7w		> 0.90	<15%			64	115
9w		> 0.90	<15%			65	115
12w		> 0.90	<15%			80	118

Lumen Output: 80-100 Lumens/Watt

LED Type	LED Make	Secondary Optics	CRI	Optics Efficacy	Main Housing	IP Protection-Complete Luminaire
Discrete	Everlight/Edison	Diffuser made in Polycarbonate	> 80	> 80-90	AL. Extrusion Main Housing + PC	IP20

Mounting Type	Driver Provision	Powder Coating	Base Available
Surface Type	Integrated in Housing	White	B-22



- BIS approved Drivers
- Under voltage protection, Over voltage protection
- Wide operating voltage range (90-300V AC)
- Over temperature protection
- Short circuit protection
- 2.5kV Surge Protection up to 48W | 4-10kV for 60W & above

Area of applications-

Home | Factories | Business Centres | Offices | School & College | Café & Restaurants | Shopping Arcades | Hotel & Resorts | Theatres | Retail Shops | Modern Retail | Hospitals