



QUADRALUMEN  
LED by life


# Product TDS

Model No.: QL8801EX

Description: QL LED Bay Light

Trademark: Casalite™

## Product Dimensions



## Product Image



System Wattage (Watts)	Input Voltage (AC)	Power Factor (PF)	THD	Driver Surge Protection	CCT Available	L (MM)	Height (MM)	Width (MM)
72w	120-300	> 0.95	<10%	7Kv	5700k	325	255	302
90w						325	255	302
100w						325	255	302
120w						435	255	302
150w						435	255	302
180w						435	255	302
200w						435	255	302

Lumen Output: 95-110 Lumens/Watt

LED Type	LED Make	Secondary Optics	CRI	Optics Efficacy	Main Housing	IP Protection-Complete Luminaire
Discrete	CREE/Samsung	LED Composite PC Lenses	> 70	>100	AL. Extrusion	IP65

Mounting Type	Driver Provision	Powder Coating	Highest voltage Sustainability
Fitted with Strap & Eyebolt for suspension	Fitted on Main Housing	Black	440V for 4 Hrs



- BIS approved Drivers
- Under voltage protection, Over voltage protection
- Wide operating voltage range (90-300V AC)
- Over temperature protection
- Short circuit protection
- 2.5kV Surge Protection up to 48W | 4-10kV for 60W & above

### Area of applications-

Factory Light | Airport concourse area | Stores | Bay Lighting | Railway Coach Factories

[www.quadralumen.com](http://www.quadralumen.com) | [www.QLindia.com](http://www.QLindia.com)